Chimiver®
"Your floors partner"

Technical Datasheet

Item Code: LTAP000X | Rev.: 12-09-2024 | Ver: 3.2

LIOS TALITA PLUS

Fast drying regenerating oil for oiled wooden floors



Description

LIOS Talita Plus is a refreshing and maintenance fast drying oil for oiled wooden floors. Dull or matt surfaces can be freshened with LIOS Talita Plus.

Characteristics

Application temperature	+10°C ÷ +25°C
Application	cloth (PANNO MAINTAIN)
Thinning (if necessary)	LIOS SOLV
Coverage	30 m²/L
Storage stability	1 year (1)
Packaging	1 L
Tool cleaning	LIOS SOLV

1 *in original sealed containers at temperatures between +10°C and +25°C*

Available Versions

STANDARD: Fast drying regenerating oil for oiled wooden floors.
COLORATO: available in white color and on request.

How to use

Shake well before use. Clean the surface to be treated in proper way with LIOS Kronos and let it dry (see technical data sheet). Proceed then applying Lios Talita Plus with a cloth (PANNO MAINTAIN) in a uniform and regular way following the veins of the wood. To obtain a floor ready for heavy foot traffic and for a more uniform result, it is possible, after above 30 minutes from the LIOS Talita Plus application, proceed by polishing with a soft cloth or with a disk monobrush fitted with white felt and cloth. It is advisable to apply LIOS Talita Plus twice a year.

Notes:do not leave any excess of product on the treated surface, local stickness can be noticed. For DIY use, use as extraordinary maintenance ONCE A YEAR.

Warnings

Once the can has been opened, prolonged storage of the product may result in a surface film or total oil hardening due to its chemical nature. To avoid this unpleasant inconvenience, if you have excess Lios Talita Plus we recommend that you transfer it into a smaller container in order to better store the product. Cloths, sponges, pads used for the application (even sanding dust), must be soaked in water immediately after use in order to avoid the risk of self-ignition.Keep out of children's reach. Do not drink nor inhale. Avoid contact with eyes. Always wear a respirator (FFP2 filter half mask according to EN 149) and only work in well-ventilated environments or using additional ventilation equipment. It is advisable to wear work clothes, safety glasses and gloves that are resistant to chemical agents.

Label elements

· *For more information about the safe use of the product it is recommended to consult the latest version of the Safety Data Sheet.*

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:

http://www.chimiver.com/tds/EN_LIOS_TALITA_PLUS.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.

CHIMIVER PANSERI S.p.A. | Via Bergamo, 1401 | 24030 Pontida (BG) | ITALY | Tel: +39 035 795031 | Fax: +39 035 795556 | chimiver.com | info@chimiver.com
All rights reserved. Any reproduction is forbidden without authorization.