MAINTENANCE OIL

Ideal for refreshing and maintaining Polyx®-Oil surfaces.


3079 Clear Matt


3081 Clear Satin


3098 Clear Semi-matt (R9)

3440 White Transparent





1 COAT

Product description:
Osmo Maintenance Oil is for the initial and routine maintenance of oiled and waxed wooden flooring. Dull and matt flooring is refreshed with Osmo Maintenance Oil. By applying Maintenance Oil at the right time, time-consuming sanding works and renovation can be avoided. Also suitable for changing the sheen of intact surfaces treated with Osmo Polyx®-Oil. Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant to wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots. The dry coating is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

Recommended use:
For the maintenance and care of all wooden flooring treated with Polyx®-Oil: solid wood, plank, parquet, strip, OSB and cork flooring, as well as stairs and furniture surfaces. Highly recommended for public interiors (e.g. restaurants, museums and other high traffic floors).

Ingredients:
Based on natural plant oils (sunflower oil, soybean oil, thistle oil) and waxes, paraffin, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free). VOC classification in compliance with EU regulations (2004/42/EC): out of scope. Detailed declaration of ingredients available upon request.

Technical Data:
Specific gravity: 0.85-0.95 g/cm³
Viscosity: 40-60s DIN 53211/3 mm
Odour: faint/mild, odourless after drying
Flashpoint: > 60 °C, acc. DIN EN ISO 2719
pH value: not required

Storage:
5 years and longer if stored in the closed original can. If thickened by frost, store at room temperature for 24 hours prior to use.

Surface Preparation:
The oiled wood surface must be clean, dry and free of dust. Clean the surface thoroughly with Osmo Intensive Cleaner and rinse (damp mop) with clear water.
The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

Methods of Application:
Osmo Maintenance Oil is ready to use. Before use shake well, or stir larger containers (2.5 l or 10.0 l) well. With Osmo Flooring Brush, Flat Brush, a trowel or Osmo Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and buff with a white pad. Remove excess product. For smaller areas, Osmo Maintenance Oil can be applied with a lint-free cloth. Ventilate well while drying.

Osmo Holz und Color GmbH & Co. KG · Affhüppen Esch 12 · D-48231 Warendorf
Phone +49 (0)2581/922-100 · Fax +49 (0)2581/922-200 · info@osmo.de · **www.osmo.de**

Cleaning of tools:
With Osmo Brush Cleaner (free of aromatic compounds).

Drying time:
Approx. 3-5 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times.

Coverage:
Product coverage for 1 coat is 40-60 m²/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

Note:
If the wood is raw or already greyed, the surface must be sanded and treated with Osmo Polyx®-Oil.

Caution:
Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

Disposal:
Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 12). Only completely emptied cans can be recycled.

Colour tone:
3079 Clear Matt
3081 Clear Satin
3098 Clear Semi-matt (R9)
3440 White Transparent

Size:
1.0 l; 2.5 l; 10 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 09/20

Osmo Holz und Color GmbH & Co. KG · Affhüppen Esch 12 · D-48231 Warendorf
Phone +49 (0)2581/922-100 · Fax +49 (0)2581/922-200 · info@osmo.de · **www.osmo.de**